



DESCRIPTION

The OFC-48K-C is a compact and portable cleaver that is designed for field usage. With its robust and stable high quality build material the cleaver offers a consistent fiber cleave result. OFC-48K-C fiber adaptor support with 4 in 1 cleave operation for 0.25 mm, 0.9mm, 2 x 3mm drop cable and 2 mm fiber cable.

FEATURES

- Multi-fiber holder clamp which supports 0.25 mm, 0.9mm, 2 x 3mm drop cable & 2mm cord cable.
- Used for single fiber cleaving and compatible with ribbon fiber cleaving adaptors
- Reduced cleaving steps and offer better cleave consistency by utilizing auto anvil drop

STANDARD ACCESSORIES

- Single Fiber Adapter (0.25 mm 0.9mm, 2 x 3mm drop cable & 2mm cord cable)
- Cleaver Blade
- Soft Carrying Case
- Built in Fiber Bin Collector
- Built in blade adjustment Allen Key

SPECIFICATIONS

Model	OFC-48K-C
Cleaver Dimensions (W x L x H) (mm)	60 x 66 x 52
Weight (g)	250
Cleaver Body Material	Aluminum Alloy
Blade Material	Tungsten Steel
Coating Diameters (mm)	0.25mm, 0.90mm, 2mm(Cord), 2 x 3mm (Drop cable)
Cladding Diameter (mm)	0.125
Cleave Lengths (mm)	5 to 20
Typical Cleave Angle (°)	90 ± 0.5
Typical Blade Life	48,000 Fiber Cleave
Number of Steps for Cleave	2
Blade Adjustments	Rotational & Height
Fiber Collector	Included
Soft Carrying Case	Included
Soft Carrying Material	Polypropylene
Soft Carrying Case Dimension (W x L x H) (mm)	78x105 x60
Operating Condition	-10 to 50 °C , Humidity < 95%
Storage Condition	-30 to 70 °C , Humidity < 95%
Warranty	1 year

ORDERING INFORMATION

Part No	Description
OFC-48K-C	Economical Single Fiber Cleaver with Fiber Collector
AX-48K-CB	Fiber Cleaver Replacement Blade

Remark : For Ribbon Fiber Cleaver, please contact us at sales@kabex.com.my

Note : Specifications are subject to change without prior notice